



技术参数:

插芯:

- 插针数: 6/6+PE
- 额定电流:
 - 电力区: 40A
 - 信号区: 16A
- 额定电压:
 - 电力区: 690V
 - 信号区: 400V
- 额定脉冲电压:
 - 电力区: 8kV
 - 信号区: 6kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V/600V
- 绝缘阻抗: $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

插针:

- 接线方式: 螺钉连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻:
 - 强电针: $<0.3\text{m}\Omega$
 - 信号针: $<1\text{m}\Omega$
- 线径范围:
 - 强电针: $4-10\text{mm}^2(12-8 \text{ AWG})$
 - 信号针: $1-2.5\text{mm}^2(18-4 \text{ AWG})$
- 拧紧力矩:
 - 强电针:
 - $\text{mm}^2: 1.5 \ 2.5 \ 4 \ 6 \ 10 \ 16$
 - $\text{N}\cdot\text{m}: 1.2 \ 2 \ 3 \ 3 \ 3 \ 3$
 - 信号针: $0.5\text{N}\cdot\text{m}$

Technical specification:

Insters:

- No. of contact: 6/6+PE
- Rated current:
 - Power area: 40A
 - Signal area: 16A
- Rated voltage:
 - Power area: 690V
 - Signal area: 400V
- Rated impulse voltage:
 - Power area: 8kV
 - Signal area: 6kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V/600V
- Insulation resistance: $>10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: >500
- Contacts:
 - Terminal: screw terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance:
 - Power contacts: $<0.3\text{m}\Omega$
 - Signal contacts: $<1\text{m}\Omega$
 - Wire gauge:
 - Power contacts: $4-10\text{mm}^2(12-8 \text{ AWG})$
 - Signal contacts: $1-2.5\text{mm}^2(18-4 \text{ AWG})$
 - Tightening tourque:
 - Power contacts:
 - $\text{mm}^2: 1.5 \ 2.5 \ 4 \ 6 \ 10 \ 16$
 - $\text{N}\cdot\text{m}: 1.2 \ 2 \ 3 \ 3 \ 3 \ 3$
 - Signal contacts: $0.5\text{N}\cdot\text{m}$

					表面处理 Finish	-			图号 Drawing No.	-	
					材料 Material	-			产品代号 Part Code	HWK-006/6-M	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	2096062101
绘图 Drawn		姓名/Name	日期/Date	姓名/Name	日期/Date	2:3	V1.0	100.4g	-	产品名称 Part Name	-
审核 Checked			18.10.2010								
工艺 Process				批准 Approved	18.10.2010						
					All Dimensions in mm Original Size DIN A 4				浙江西霸士电气有限公司		