



技术参数:

- 插芯:
- 插针数: 3/4
 - 额定电流:
 - 电力区: 40A
 - 信号区: 10A
 - 额定电压: 830V
 - 额定脉冲电压: 8kV
 - 污染等级: 3
 - 依据UL的额定电压: 600V
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: > 500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 - 镀银
 - 镀金
 - 接触电阻:
 - 电力区: $< 1\text{m}\Omega$
 - 信号区: $< 3\text{m}\Omega$
 - 线径范围:
 - 电力区: 1.5-6mm²(16-10 AWG)
 - 信号区: 0.14-2.5mm²(26-14 AWG)
 - 最大电缆直径: 5mm
 - 工具:
 - 冷压钳:
 - TL02-0G(1.5-6mm²)
 - TL02-3G(4/6/10mm²)
 - TL02G(0.14-4mm²)
 - 退针器:
 - TL06G(40A冷压针)
 - TL00(10A冷压针mm²)

Technical specification:

- Inserts:
- No. of contact: 3/4
 - Rated current:
 - Power contacts: 40A
 - Signal contacts: 10A
 - Rated voltage: 830V
 - Rated impulse voltage: 8kV
 - Pollution degree: 3
 - Rated voltage acc.to UL: 600V
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: > 500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 - hard-silver plated
 - hard-gold plated
 - Contact resistance:
 - Power contacts: $< 1\text{m}\Omega$
 - Signal contacts: $< 3\text{m}\Omega$
 - Wire gauge:
 - Power contacts: 1.5-6mm²(16-10 AWG)
 - Signal contacts: 0.14-2.5mm²(26-14 AWG)
 - Tools:
 - Crimp contact tool:
 - TL02-0G(1.5-6mm²)
 - TL02-3G(4/6/10mm²)
 - TL02G(0.14-4mm²)
 - Contact removal tool:
 - TL06G(for crimp contacts 40A)
 - TL00(for crimp contacts 10A)

				表面处理 Finish	-				图号 Drawing No.	-	
				材料 Material	-				产品代号 Part Code	HMK-003/4-MC	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date				产品料号 Part No.	2111074101	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	-
绘图 Drawn		18.10.2010	标准化 Stand.	-	-	1:1	V1.0	12.8g	-		
审核 Checked		18.10.2010									
工艺 Process	-	-	批准 Approved		18.10.2010			All Dimensions in mm Original Size DIN A 4		浙江西霸士电气有限公司	