



技术参数:

- 插针数: 2
- 额定电流: 40A
- 额定电压: 1000V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL的额定电压: 600V
- 绝缘阻抗:  $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数:  $>500$

插针:

- 接线方式: 轴向螺栓连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻:  $<1\text{m}\Omega$
- 线径范围: 2.5-8mm<sup>2</sup>
- 内六角扳手: HEXA-D1
- 剥线长度:
  - mm<sup>2</sup>: 2.5 4 6 10
  - mm: 5<sup>+1</sup> 5<sup>+1</sup> 8<sup>+1</sup> 11<sup>+1</sup>
- 拧紧力矩:
  - mm<sup>2</sup>: 2.5 4 6 10
  - N·m: 1.5 1.5 2 2

Technical specification:

- Inserts:
  - No. of contact: 2
  - Rated current: 40A
  - Rated voltage: 1000V
  - Rated impulse voltage: 8kV
  - Pollution degree: 3
  - Rated voltage acc.to UL: 600V
  - Insulation resistance:  $>10^{10}\Omega$
  - Material: polycarbonate
  - Colour: RAL 7032(light grey)
  - Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
  - Flammability acc.to UL 94: V0
  - Mating cycles:  $>500$

Contacts:

- Terminal: axial screw terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance:  $<1\text{m}\Omega$
- Wire gauge: 2.5-8mm<sup>2</sup>
- Hexagonal driver: HEXA-D1
- Stripping length:
  - mm<sup>2</sup>: 2.5 4 6 10
  - mm: 5<sup>+1</sup> 5<sup>+1</sup> 8<sup>+1</sup> 11<sup>+1</sup>
- Tightening torque:
  - mm<sup>2</sup>: 2.5 4 6 10
  - N·m: 1.5 1.5 2 2

					表面处理 Finish	-			图号 Drawing No.	-
					材料 Material	-			产品代号 Part Code	HMK-002.1-M
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date			产品料号 Part No.	2113022101
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name
绘图 Drawn		18.10.2010	标准化 Stand.	-	-	1:1	V1.0	25.4g	-	-
审核 Checked		18.10.2010								
工艺 Process	-	-	批准 Approved		18.10.2010			All Dimensions in mm Original Size DIN A 4		浙江西霸士电气有限公司